

## SPM2 Polishing Machine

### Features:

- Standards-conforming polishing of individual connectors
- High reproducibility of polishing result
- Robust and durable construction
- Easy to operate
- Linear adjustable and constant polishing pressure
- Polishing time < 2 min
- Choice of power supply or battery operation permits flexible application
- Suitable for all standard connectors
- Free of maintenance



### Use:

- Field and laboratory
- FTTX
- Reconditioning of individual connector

### Technical Data

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| Part number                             | SPM2-0001-00V3                  |
| Electrical connection                   | 230V AC, 50Hz/ 12V power supply |
| Power input                             | typically 300 mA                |
| Service with life accumulator           | ~ 500 Polituren                 |
| Adjustable polishing pressure           | 0 - 3 N                         |
| Operating temperature                   | -10°C bis + 50°C                |
| Relative humidity                       | max. 85 %                       |
| Measurements (breadth x depth x height) | 120 mm x 120 mm x 170 mm        |
| Weight                                  | ~ 3,5 Kg                        |

### Holding jigs

SC, LC, ST, FC, DIN, FSMA, MU, E2000, Ferrule Ø 1,25 mm, Ferrule Ø 2,5 mm

### Polishes

SPC, UPC, APC